

Alucast Upright Security Covers



Overview



APPLICATIONS

- Monitoring wells
- Inclinometer boreholes
- Piezometers
- Borehole rod extensometers

FEATURES

- High visibility
- Water resistant
- Labelled for extra security
- H-20 rated
- Lockable

Alucast Upright Aluminium Security Covers provide lightweight water resistant security and are particularly useful where easy location of the borehole is required, such as a field or where vegetation is likely to obscure the borehole location.

Manufactured in aluminium with a corrosion resistant coating, they make a convenient lightweight alternative to traditional heavy steel covers.

They are fitted with a simple hinged lid and secured with a heavy-duty padlock and are designed to be set into concrete the external lugs near the base provide a key into the concrete and prevent unauthorised removal.



Geosense Ltd, Nova House, Rougham Industrial Estate, Rougham, Bury St Edmunds, Suffolk IP30 9ND, England

www.geosense.com e sales@geosense.com
t+44(0)1359 270457

SPECIFICATIONS

Nominal Size (inch)	Flange Diameter (mm)	Flange Thickness (mm)	Skirt Diameter (mm)	Height Clear (mm)	Open Aperture (mm)	Weight (kg)
6	150	22	137	175	90	1.46
8	195	24	165	225	110	2.67
10	245	22	220	325	155	4.5

Specifications are subject to change without notice and should not be construed as a commitment by Geosense. Geosense assumes no responsibility for any errors that may appear in this document. In no event shall Geosense be liable for incidental or consequential damages arising from the use of this document or the systems described in this document. All Content published or distributed by Geosense is made available for the purposes of general information. You are not permitted to publish our content or make any commercial use of our content without our express written consent. This material or any portion of this material may not be reproduced, duplicated, copied, sold, resold, edited, or modified without our express written consent.